



The versatility of the DTC4500 is unsurpassed from loyalty cards to sophisticated access cards with embedded electronics. Empowered by an extremely robust and highly-reliable print engine, this high-volume printer delivers speed, power and versatility rolled into one.

VYKON DTC4500 Printer



Overview

The FARGO® DTC4500 is built with Genuine HID™ technology and is fully interoperable with other products in the HID ecosystem, and integrates seamlessly with Vykon Enterprise Security.

The DTC4500 offers field-upgradable options for migration to higher levels of security in the future:

Optional card lamination options are available for applying overlaminates to produce high-secure cards that resist forgery and increase card durability. Unique, dual-sided simultaneous lamination also saves time with increased throughput.

Dual-sided printing module option provides more space for card holder information and security features like duplicate photo and digital-signature.

The versatility of the DTC4500 is unsurpassed from loyalty cards to sophisticated access cards with embedded electronics. Empowered by an extremely robust and highly-reliable print engine, this high-volume printer delivers speed, power and versatility rolled into one.

High capacity ribbons enable the DTC4500 to print twice as many full color cards than most printers before the ribbon has to be changed, providing continuous high quality-card printing and encoding.

Features

- High-volume performance – Built for organizations requiring robust, high-volume printing every day. Standard features include high-capacity ribbon supplies and dual-input card hoppers that allow for maximum card input capacity and management of multiple card types
- Maximum security – Optional single- or dual-sided simultaneous lamination offers enhanced card security and durability
- Highly versatile – The modular design allows organizations to build upon their investment by adding field-upgradable modules, such as dual-sided printing and technology card encoding
- Earth friendly – ENERGY STAR® certified for efficient energy consumption
- Built-in security with password-protected printer operation for a cost effective and dynamic increase in card security.
- SmartScreen™ graphical display provides easy-to-follow prompts to be sure you'll always know the status of the printer.
- Standard dual-input card hopper for increased capacity or management of multiple card types.
- Easy integration into existing IT infrastructures through the built-in Ethernet and USB connection, allowing for centralized or remote ID card issuance.
- Industry's first inline card printing and technology card encoding with one connection using USB or Ethernet connectivity.
- Fully compatible with Asure ID® card personalization software for badge design, database management and technology card encoding.



Ordering Information

Part #	Description
DTC 4500 Printers	
SEC-PID-049000	Base Model, USB and Ethernet Printer with Two Year Printer Warranty, Single Sided Printing
SEC-PID-049100	Base Model, USB and Ethernet Printer with Two Year Printer Warranty, Dual Sided Printing
SEC-PID-049400	Base Model, USB and Ethernet Printer with Two Year Printer Warranty, Single Side Lamination
SEC-PID-049500	Base Model, USB and Ethernet Printer with Two Year Printer Warranty, Dual Side Lamination
DTC 4500 Printer Upgrades	
SEC-PID-047720	Dual-Side Printing Module Field Upgrade
SEC-PID-047723	Single-Sided Lamination Module (Dual-Side Printing Module Included) Field Upgrade
SEC-PID-047724	Dual-Sided Simultaneous Lamination Module (Dual-Side Printing Module Included) Field Upgrade
Printer Ribbons	
SEC-PID-045200	YMCKO: Full-color ribbon with resin black and clear overlay panel – 500 images
SEC-PID-045201	Premium Black (K) – 3000 images
SEC-PID-045202	Standard Black (K) – 3000 images
SEC-PID-045203	Blue – 2000 images
SEC-PID-045204	Green – 2000 images
SEC-PID-045205	Red – 2000 images
SEC-PID-045206	White – 2000 images
SEC-PID-045207	Gold – 1000 images
SEC-PID-045208	Silver – 1000 images
SEC-PID-045210	YMCKOK: Full-color ribbon with two resin black panels and clear overlay panel – 500 images
SEC-PID-045215	YMCKK: Full-color ribbon with two resin black panels – 500 images
Replacement Parts and Cleaning Supplies	
SEC-PID-047500	Thermal Printhead
SEC-PID-086177	Cleaning Kit – includes 2 Printhead Cleaning Pens, 10 Cleaning Cards, 10 Cleaning Pads
SEC-PID-047725	Cleaning Rollers - 3 pack
SEC-PID-086131	Extra Cleaning Cards (double sided), 50 count
SEC-PID-082133	Iso-Propyl Alcohol Cleaning Cards - 10 pack
Photo Capture Equipment	
SEC-PID-041838	Logitech Webcam C310, integrated microphone, and TWAIN compatible drivers
SEC-PID-086100	Lt. Blue wrinkle-resistant nylon micro-suede material measuring 34 X 28".
SEC-PID-086101	White wrinkle-resistant nylon micro-suede material measuring 34 X 28".
SEC-PID-086102	Sturdy, lightweight easy to assemble and dismantle. Can be used for both sitting or standing applications.
SEC-PID-086103	Tripod for desktop applications. 11"-20" working range with 3-way panhead, bubble level, gear elevator and rubber feet.
SEC-PID-086104	Tripod for floor-standing applications. 25"-59" working range with 3-way panhead, bubble level, gear elevator and rubber feet



Specifications

Print Method	Dye-Sublimation / Resin Thermal Transfer
Resolution	300 dpi (11.8 dots/mm) continuous tone
Colors	Up to 16.7 million / 256 shades per pixel
Print Ribbon Options	<p>Full-color with resin black and overlay panel, YMCKO*, 500 prints</p> <p>Full-color half-panel with resin black and overlay panel, YMCKO*, 850 prints</p> <p>Full-color with two resin black panels and overlay panel, YMCKOK*, 500 prints</p> <p>Full-color with fluorescing, resin black and overlay panel, YMCFKO*, 500 prints</p> <p>Full-color with fluorescing, two resin black panels and overlay panel, YMCFKOK*, 400 prints</p> <p>Full-color with two resin black panels and overlay panel, YMCKK*, 500 prints</p> <p>Resin black and overlay panel, KO*, 1250 prints</p> <p>Dye-sublimation black and overlay panel, BO*, 1250 prints</p> <p>Resin black (standard and premium), 3000 prints</p> <p>Resin green, blue, red, white, silver and gold, 2000 prints</p> <p>Rewrite technology - no ribbon required</p>
Print Speed**	7 seconds per card (K*); 12 seconds per card (KO*); 24 seconds per card (YMCKO*); 31 seconds per card (YMCKOK*)
Accepted Standard Card Sizes	CR-80 (3.375" L x 2.125" W / 85.6 mm L x 54 mm W); CR-79 Adhesive Back (3.313" L x 2.063" W / 84.1 mm L x 52.4 mm W)
Print Area	CR-80 edge-to-edge (3.36" L x 2.11" W / 85.3 mm L x 53.7 mm W); CR-79 (3.3" L x 2.04" W / 83.8 mm L x 51.8 mm W)
Accepted Card Thickness	Print Only: .009" - .040" / 9 mil - 40 mil / .229 mm - 1.016 mm; Print/Lamination: .030" - .040" / 30 mil - 40 mil / .762 mm - 1.02 mm
Accepted Card Types	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; optical memory cards with PVC finish; rewrite
Input Hopper Card Capacity	Dual-Input Card Hopper (200 cards)
Output Hopper Card Capacity	Up to 100 cards (.030" / .762 mm)
Reject Hopper Card Capacity	Up to 100 cards (.030" / .762 mm) - same-side input/output card hopper or lamination module required
Card Cleaning	Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon change
Memory	32 MB RAM
Software Drivers	Windows® XP / Vista™ (32 bit & 64 bit) / Server 2003 & 2008 / Windows® 7 / MAC OS X 10.5/10.6 / Linux***
Interface	USB 2.0 and Ethernet with internal print server
Operating Temperature	65° to 80° F / 18° to 27° C
Humidity	20–80% non-condensing
Dimensions	<p>Single-Sided Printer: 9.8" H x 18.1" W x 9.2" D / 249 mm H x 460 mm W x 234 mm D</p> <p>Dual-Sided Printer: 9.8" H x 18.7" W x 9.2" D / 249 mm H x 475 mm W x 234 mm D</p> <p>Printer + Lam: 18.9" H x 18.7" W x 9.2" D / 480 mm H x 475 mm W x 234 mm D</p>
Weight	Single-Sided Printer: 9lbs / 4.1 Kg; Dual-Sided Printer: 11lbs / 5 Kg; Printer + Lam: 20 lbs / 9.1 Kg
Agency Listings	Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KCC
Environmental Features	All configurations without a lamination module are ENERGY STAR® qualified printers

Supply Voltage	100-240 VAC, 3.3 A
Supply Frequency	50 Hz / 60 Hz
Warranty	Printer – Two years; Printhead – Two years, unlimited pass with UltraCard™
Encoding Options	125 kHz (HID Prox) reader; 13.56 MHz (iCLASS®, MIFARE®, ISO 14443 A/B, ISO 15693) read/write encoder; Contact Smart Card Encoder reads from and writes to all ISO7816 1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards; ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2 and 3
Options	Single Wire Ethernet and USB 2.0 interface for inline printing and encoding (note: single wire Ethernet encoding is only available for iCLASS® and contact smart card encoding); Dual-Sided Printing Module - Upgradable; Same-Side Input/Output Card Hopper - Upgradable; Contactless Smart Card Encoding - Upgradable; Contact Smart Card Encoding - Factory Upgrade; Magnetic Stripe Encoding - Upgradable; Printer Cleaning Kit; Single- or dual-sided simultaneous lamination - Upgradable
Software	Swift ID™ Embedded Badging Application, FARGO Workbench Diagnosis Utility
Display	User friendly, SmartScreen™ graphical display
Printer Security	Printer access password protected; Kensington® lock compatibility

* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, O=Overlay, B=Dye Sublimation Black.

** Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.

***Linux versions: Ubuntu 8.04/9.04, Red Hat 5, Fedora 7/8/9/10/11, Open Suse 10.3, Debian 5.03/5.04, Mandiva one 2009

