



The JACE-603 is ideal for smaller facilities, remote sites, and for distributing control and monitoring throughout large facilities. It is also ideal for managing and controlling today's energy applications.

VYKON JACE-603



Overview

The VYKON JACE-603 is an embedded controller/server platform designed for remote monitoring and control applications. The unit combines integrated control, supervision, data logging, alarming, scheduling and network management functions, integrated IO with Internet connectivity and web serving capabilities in a small, compact platform. The JACE-603 makes it possible to control and manage external devices over the Internet and present real time information to users in web-based graphical views.

In addition to supporting the Niagara^{AX} Framework applications, the JACE-603 can optionally support Niagara R2 applications. This option provides the ideal platform for projects currently utilizing Niagara R2 technology where a cost effective migration to Niagara^{AX} Framework is desired. The Niagara^{AX} Framework compatible platform can be installed and optionally configured to support a facility utilizing a Niagara R2 Framework application today. At a later date, the facility can migrate to a Niagara^{AX} Framework application, thus spreading the cost of the migration across multiple phases.

The JACE-603 is part of the VYKON portfolio of Java-based controller/server products, software applications and tools, designed to integrate a variety of devices and protocols into unified, distributed systems. VYKON products are powered by the Niagara^{AX} Framework®, the industry's leading software technology that integrates diverse systems and devices into a seamless system. Niagara^{AX} supports a range of protocols including LonWorks®, BACnet®, Modbus, oBIX and many Internet standards. The Niagara^{AX} Framework also includes integrated management tools to support the design, configuration and maintenance of a unified, real-time controls network. The integral I/O, LonWorks® FTT-10A port, RS-485 port, RS-232 port, metal enclosure and line voltage input power supply, make this platform ideal for a wide variety of integration applications.

Applications

The JACE-603 is ideal for smaller facilities, remote sites, and for distributing control and monitoring throughout large facilities. It is also ideal for managing and controlling today's energy applications. On-board universal inputs and Form C relay outputs are available for applications where local control is required. The JACE-603 includes one LonWorks® FTT-10A port and one RS-485 port providing support for a wide range of field buss connections to remote I/O and stand-alone controllers. In small facility applications, the JACE-603 is all you need for a complete system. The JACE-603 serves data and rich graphical displays to a standard web browser via an Ethernet LAN or remotely over the Internet. In larger facilities, multi-building applications and large-scale control system integrations, VYKON AX Supervisor™ software can be used to aggregate information (real-time data, history, alarms, etc.) from large numbers of JACE-603 JACEs into a single unified application.

Features

- Embedded PowerPC Platform@ 524MHz
- One LON FTT-10A port for LON device integration
- Direct, on-board I/O with six universal inputs, and 4 Form C relay outputs
- One RS-485 port for connection to open and proprietary protocol devices
- One RS-232 port for Integration or diagnostics and troubleshooting
- Web UI services to support many simultaneous users over the intranet or Internet via a standard web browser
- One Niagara^{AX} Framework option slot supporting NPB-XXX option modules. (Not compatible with R2 stations.)

Ordering Information

Part Number	Part Description
J-603	Base Unit including two Ethernet ports, one RS-232 port, one RS-485 port, one LonWorks® FTT-10A port, six universal inputs, and four Form C relay outputs. Web User Interface and Niagara Connectivity included. oBIX Client/Server, BACnet MSTP, BACnet IP Client, and Lonworks FTT-10A driver included. Includes steel wall-mountable enclosure with 120 V power supply and backup battery.
J-603I	J-603 with 230 VAC power supply for international installations
R2-6XX	Capability to utilize a Niagara R2 based application. Requires R2 version 301.535 or higher. <i>*Note: For replacement of R2 JACE platforms the VYKON 603/645 order form must be submitted at the time of order to transfer license features. Restricted features may not be transferrable.</i>
NPM-256	Upgrade RAM memory to 256 MB DDR.

Note: Refer to current price list for additional options.

Specifications

Platform

- PowerPC 440 524 MHz processor
- 128MB DDR RAM & 128 MB Serial Flash
- SLA Battery Backup
- Optional 256 MB DDR RAM
- Real-time clock

Communications

- Two 10/100 Mb Ethernet port – RJ-45 connection.
- One RJ-45 connector for RS-232 port.
- One screw terminal RS-485 port (up to 115,200 baud for MSTP).
- One LonWorks port – FTT-10A with Weidmuller connector.
- One Niagara^{AX} option slot (see available option modules below). Not compatible with R2 stations.

Battery Backup

- Battery backup provided for all on board functions.
- Battery is monitored and trickle charged.
- Battery maintains processor operation through power failures for a pre-determined interval. In the event of extended loss of power, the battery maintains operation long enough to save all data from memory and perform a normal system shutdown.

Available Niagara^{AX} Option Modules

- | | |
|----------------|-----------------------------------|
| • NPB-LON | LON® Card |
| • NPB-232 | RS 232 Card |
| • NPB-2X-485 | Dual Port RS 485 Card |
| • NPB-GPRS-W | GPRS Modem with Wyleless SIM Card |
| • NPB-ZWAVE-US | ZWAVE Card/Driver Bundle US |
| • NPB-ZWAVE-EU | ZWAVE Card/Driver Bundle EU |
| • NPB-SED-001 | Sedona Wired/Wireless Card |

Optional Remote I/O Expansion Module (Niagara^{AX} applications only)

- IO-16-485 - Includes 8 Universal Inputs, 4 Form A Relay Outputs, and 4 0-10 VDC Analog Outputs. May be mounted remotely. Communicates via a dedicated RS-485 port. JACE-6 platforms support up to 16 Remote I/O modules.

Operating System

- QNX Real-time Operating System
- Sun HotSpot JVM Java Virtual Machine
- Niagara^{AX} 3.6.47 or later
- Niagara R2 301.535 or later

Power Supply

- J-603: 120VAC, 50/60 Hz.,
- J-603I: 230VAC, 50/60 Hz,
- 25 VA maximum.
- Lead wires for hot/neutral (wire nut), stud for ground connection. J-603I has two-screw terminal strip for AC power connections, plus a stud for ground.

Inputs/Outputs

- Four Form C (SPDT) relay outputs rated for 24 VAC/DC @ 2 Amps resistive.
 - One LED indicator for each relay.
- Six Universal Inputs
 - 10K Ohm Type III (10K 4A1-International) Thermistor, sensor range -23.3°C to 57.2°C (-10° to 135° F). Input accuracy ±1% of span.
 - 0–10 volt or 4/20 mA accuracy is ±2% of span, without user calibration. Uses an external resistor for current input (four provided). Self powered or board powered sensors accepted.
 - Dry contacts 20 Hz max. frequency (25 ms minimum pulse width). 3V open circuit, 300 mA short-circuit current.
- Board provides 20 VDC @ 80 mA to drive 4/20 mA powered sensors.
- 24 VDC terminal and external resistor can be used if monitoring contacts that require higher voltages or higher current.
- All I/O connections are screw terminals on 0.2" centers.

Chassis

- Housed in metal enclosure, Intended for indoor wall mounting only.
- Cooling: Internal air convection.
- Dimensions: 11" wide X 14" high X 2.5" deep (27.94 cm wide X 35.56 cm high X 6.35 cm deep).
- Weight: Net 4 lbs. (1.814 kg), Gross 5 lbs. (2.268 kg).

Environment

- Operating temperature range: 0° to 50°C (32°F to 122°F)
- Storage Temperature range: 0° to 70°C (32°F to 158°F)
- Relative humidity range: 5% to 95%, non-condensing

Other

- Maximum Lon devices = up to 127
- Maximum MSTP devices per RS-485 port = 31 full load, 63 half load, and 127 quarter load
- RS-232/RS-485 Port speeds supported are:
 - 4800 baud
 - 9600 baud
 - 19,200 baud
 - 38,400 baud
 - 57,600 baud
 - 76,800 baud

Agency Listings

- RoHS Compliant
- BTL
- UL 916
- C-UL listed to Canadian Standards Association (CSA) C22.2 No. 205-M1983 "Signal Equipment"
- FCC part 15 Class B
- CE



Architecture

